

View Online at <https://aerobasegroup.com/nsn/5925-01-184-0633>

Overall Length:

50.8 millimeters

Body Width:

22.61 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

23.01 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

39.9 millimeters

Fragility Factor:

Moderately rugged

End Application:

3805-01-153-1854

Mounting Surface To Terminal End Distance:

32.13 millimeters

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

600.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

130.0 single location

Reset Method:

Automatic

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.164 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

5.500 at 200 pct single location and 55.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Shock resistant and vibration resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Criticality Code Justification:

Feat

Special Features:

Self-locking nuts for 8-32 screws

Unpackaged Unit Weight:

1.500 ounces

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0