

View Online at <https://aerobasegroup.com/nsn/5925-01-184-5359>

Body Style:

Rectangular dimensional envelope

Overall Length:

Between 1.969 inches and 2.031 inches

Overall Height:

Between 1.169 inches and 1.231 inches

Overall Width:

Between 1.822 inches and 1.884 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 clip

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

1.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

2.200 at 200 pct single location and 20.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Frequency In Hertz:

50.0 single location or 60.0 single location

Unpackaged Unit Weight:

2.500 ounces

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0