NSN 5925-01-184-6912

Circuit Breaker - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5925-01-184-6912

Body Style:
Single pole type
Overall Length:
1.750 inches
Overall Width:
0.563 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
0.780 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 1.950 inches and 1.970 inches
Switch Contact Arrangement:
Single pole, double throw
Fragility Factor:
Moderately rugged
Boss Height:
0.406 inches
Mounting Surface To Terminal End Distance:
2.250 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
1 threaded bushing
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
5.0 amperes ac single location
Operating Voltage Type And Rating Per Pole In Volts:
250.0 ac single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1500.0 ac single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal-magnetic single location
Trip Release Characteristic:

Time delay single location

NSN 5925-01-184-6912

Circuit Breaker - Page 2 of 3



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
140.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push button
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Auxiliary Switch Function And Quantity:
1 alarm
Thread Size:
0.375 inches
Switch Location And Position Designation:
Internal at pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
10.000 at 200 pct single location and 40.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Waterproof and dustproof
Trip Release Ambient Tempurature Rating:
70.0 degrees celsius single location
Switch Terminal Type:
Tab, solder lug
Switch Current Rating And Type In Amps:
1.0 ac
Switch Voltage Rating And Type In Volts:
250.0 ac
Frequency In Hertz:
60.0 single location
Unpackaged Unit Weight:
0.062 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5925-01-184-6912

Circuit Breaker - Page 3 of 3



Fiig:

A030a0