NSN 5925-01-186-4601



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-186-4601 **Body Style:** Multipole-single actuator type **Body Length:** 6.562 inches **Body Width:** 4.125 inches **Body Height:** 3.812 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 5.125 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.376 inches **Unthreaded Mounting Hole Diameter:** 0.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 4.875 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.376 inches **Boss Height:** 0.219 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 30.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:**

Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations

NSN 5925-01-186-4601

Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Shunt trip all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
120.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
3.500 pounds
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0