

View Online at <https://aerobasegroup.com/nsn/5925-01-186-4602>

Body Style:

Multipole-single actuator type

Body Length:

6.562 inches

Body Width:

4.125 inches

Body Height:

2.625 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

5.125 inches

Center To Center Distance Between Terminals Parallel To Width:

1.376 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.876 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.376 inches

Boss Height:

0.219 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

125.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Shunt trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

480.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

General purpose

Frequency In Hertz:

60.0 all locations

Unpackaged Unit Weight:

3.500 pounds

Terminal Type And Quantity:

6 compression and 3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0