# NSN 5925-01-186-4603

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-186-4603

# **Body Style:**

Multipole-single actuator type

### **Body Length:**

6.562 inches

# Body Width:

4.125 inches

#### **Body Height:**

3.812 inches

#### **Case Material:**

Plastic

# Center To Center Distance Between Terminals Parallel To Length:

#### 5.125 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 1.376 inches

**Unthreaded Mounting Hole Diameter:** 

# 0.250 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.876 inches

# Switch Contact Arrangement:

Single pole, double throw

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.376 inches

# **Boss Height:**

0.219 inches

# Pole Quantity:

3

# Mounting Facility Type And Quantity:

4 unthreaded hole

# Storage Type:

General purpose warehouse

# Maximum Continuous Load Current Rating Per Pole:

80.0 amperes ac all locations

# **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

# Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations

# **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Magnetic all locations

#### **Trip Release Characteristic:**

Time delay all locations

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

## **Reset Method:**

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

**Actuator Function:** 

Trip-reset

**Actuator Position Designation:** 

At pole two

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip all locations

Switch Location And Position Designation:

Internal at pole three

Trip Delay Time In Seconds Per Rated Continuous Current:

360.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

General purpose

Switch Terminal Type:

Tab, solder lug

Switch Current Rating And Type In Amps:

6.0 ac and 0.25 dc

Switch Voltage Rating And Type In Volts:

240.0 ac and 250.0 dc

**Frequency In Hertz:** 

60.0 all locations

**Unpackaged Unit Weight:** 

3.500 pounds

**Terminal Type And Quantity:** 

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0