## NSN 5925-01-186-4604



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-186-4604 **Body Style:** Multipole-single actuator type **Bushing Length:** 0.495 inches **Body Length:** 2.000 inches **Body Width:** 1.515 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 1.530 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 2.232 inches **Pole Quantity: Mounting Facility Type And Quantity:** 1 threaded bushing w/panel seal Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes dc first location Operating Voltage Type And Rating Per Pole In Volts: 65.0 dc first location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 dc first location **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations

## **NSN 5925-01-186-4604** Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.500 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.120 at 200 pct all locations and 1.200 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Corrosion resistant and fungus resistant and moisture resistant
Frequency In Hertz:
50.0 second location or 60.0 second location
Unpackaged Unit Weight:
6.000 ounces
Thread Series Designator:
Un
Terminal Type And Quantity:
4 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0