## NSN 5925-01-187-0694

Circuit Breaker - Page 1 of 2

Magnetic all locations

Time delay all locations

**Trip Release Characteristic:** 



View Online at https://aerobasegroup.com/nsn/5925-01-187-0694 **Body Style:** Multipole-single actuator type **Body Length:** 6.562 inches **Body Width:** 4.125 inches **Body Height:** 3.812 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 5.125 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.376 inches **Unthreaded Mounting Hole Diameter:** 0.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 4.875 inches **Switch Contact Arrangement:** Single pole, double throw Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.376 inches **Boss Height:** 0.250 inches **Pole Quantity:** 3 **Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** 

## NSN 5925-01-187-0694

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Auxiliary Switch Function And Quantity:
1 alarm
Internal Trip Release Configuration:
Series trip all locations
Switch Location And Position Designation:
Internal at pole three
Trip Delay Time In Seconds Per Rated Continuous Current:
120.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Switch Terminal Type:
Tab, solder lug
Switch Current Rating And Type In Amps:
6.0 ac and 0.25 dc
Switch Voltage Rating And Type In Volts:
250.0 ac and 250.0 dc
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
3.500 pounds
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0