

View Online at <https://aerobasegroup.com/nsn/5925-01-188-2506>

**Body Style:**

Single pole type

**Bushing Length:**

Between 0.245 inches and 0.281 inches

**Body Length:**

Between 0.719 inches and 0.781 inches

**Body Width:**

0.593 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.285 inches and 0.315 inches

**Nonturn Device Location:**

At 12 oclock

**Nonturn Device Radius:**

0.360 inches

**Nonturn Device Diameter:**

Between 0.370 inches and 0.380 inches

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

1.590 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

3.0 amperes ac single location and 3.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac single location and 28.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2500.0 ac single location and 2500.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

145.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.438 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

5.000 at 200 pct single location and 50.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Moisture resistant and corrosion resistant and sandtight and explosion proof

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius single location

**Frequency In Hertz:**

400.0 single location

**Unpackaged Unit Weight:**

0.080 pounds

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0