

View Online at <https://aerobasegroup.com/nsn/5925-01-190-5272>

Body Style:

Rectangular dimensional envelope

Overall Length:

1.250 inches

Overall Height:

0.780 inches

Overall Width:

1.190 inches

Case Material:

Plastic

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 terminal

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

24.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

100.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

External Actuator Linkage Arrangement:

One and two linked

Auxiliary Switch Function And Quantity:

1 control

Internal Trip Release Configuration:

Shunt trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

200.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

General purpose

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0