

View Online at <https://aerobasegroup.com/nsn/5925-01-191-9675>

**Body Style:**

Single pole type

**Overall Length:**

1.438 inches

**Body Width:**

0.400 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.668 inches and 0.688 inches

**Unthreaded Mounting Hole Diameter:**

0.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 0.995 inches and 1.005 inches

**Mounting Surface To Terminal End Distance:**

1.320 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

12.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

40.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Automatic

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

3600.000 at 125 pct single location and 60.000 at 100 pct single location

**Inclosure Protection Type For Which Designed:**

General purpose

**Trip Release Ambient Tempurature Rating:**

25.0 degrees celsius single location

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0