

View Online at <https://aerobasegroup.com/nsn/5925-01-191-9675>

Body Style:

Single pole type

Overall Length:

1.438 inches

Body Width:

0.400 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

Between 0.668 inches and 0.688 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.995 inches and 1.005 inches

Mounting Surface To Terminal End Distance:

1.320 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

12.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

40.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Automatic

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

3600.000 at 125 pct single location and 60.000 at 100 pct single location

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0