

View Online at <https://aerobasegroup.com/nsn/5925-01-191-9852>

**Body Style:**

Single pole type

**Bushing Length:**

0.250 inches

**Body Length:**

0.781 inches

**Body Width:**

0.593 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.500 inches

**Mounting Surface To Terminal End Distance:**

1.343 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

7.5 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

200.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2500.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.438 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

5.000 at 800 pct pascal single location and 15.000 18 stage pascal single location

**Inclosure Protection Type For Which Designed:**

Vibration resistant

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius single location

**Special Features:**

Vibration tested

**Frequency In Hertz:**

400.0 single location

**Unpackaged Unit Weight:**

1.300 ounces

**Test Data Document:**

81343-as58091 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

2 tab w/screw

**Specification Data:**

81343-ms3320-7-1/2v professional/industrial association specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0