

View Online at <https://aerobasegroup.com/nsn/5925-01-193-7247>

Body Style:

Multipole-single actuator type

Bushing Length:

0.495 inches

Body Length:

2.000 inches

Body Width:

1.515 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.656 inches

Nonturn Device Diameter:

0.138 inches

Mounting Surface To Terminal End Distance:

2.232 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes dc first location

Operating Voltage Type And Rating Per Pole In Volts:

32.0 dc first location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1500.0 dc first location

Circuit Protection Type:

Overvoltage second location

Trip Release Method:

Magnetic second location

Trip Release Characteristic:

Time delay first location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 second location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip second location

Thread Size:

0.500 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.180 at 200 pct first location and 1.800 at 200 pct first location

Thread Series Designator:

Un

Terminal Type And Quantity:

4 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0