## NSN 5925-01-194-1538

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-194-1538

Overall Length:
15.500 inches
Overall Height:
4.750 inches
Overall Width:
9.000 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.500 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Maximum Continuous Load Current Rating Per Pole:
1400.0 amperes ac all locations and 1400.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
600.0 ac all locations and 250.0 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
42000.0 ac all locations and 20000.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations and time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
150.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
4000.000 at 200 pct all locations and 8000.000 at 200 pct all locations

77.0 degrees fahrenheit all locations

**Trip Release Ambient Tempurature Rating:** 

## NSN 5925-01-194-1538

Circuit Breaker - Page 2 of 2



	Freq	uency	In	Hertz	:
--	------	-------	----	-------	---

400.0 all locations

**Terminal Type And Quantity:** 

6 compression

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0