

View Online at <https://aerobasegroup.com/nsn/5925-01-194-7532>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.490 inches

**Body Width:**

3.030 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.940 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.062 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**End Application:**

4920-01-111-2981

**Boss Height:**

0.150 inches

**Mounting Surface To Terminal End Distance:**

2.475 inches

**Pole Quantity:**

4

**Mounting Facility Type And Quantity:**

8 threaded hole

**Features Provided:**

High inrush protection

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

5.0 amperes ac second location

**Operating Voltage Type And Rating Per Pole In Volts:**

32.0 dc third location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2000.0 dc third location

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

4 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One, two, three, and four linked

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.700 at 200 pct third location and 10.000 at 200 pct third location

**Inclosure Protection Type For Which Designed:**

Fungus proof

**Frequency In Hertz:**

50.0 second location or 60.0 second location

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

8 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0