NSN 5925-01-195-2013

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-195-2013

Body Style: Single pole type **Body Length:** 2.300 inches **Body Width:** Between 0.740 inches and 0.760 inches Case Material: Plastic **Center To Center Distance Between Terminals Parallel To Length:** Between 1.655 inches and 1.685 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** Between 1.800 inches and 1.820 inches **Boss Height:** Between 0.125 inches and 0.135 inches **Mounting Surface To Terminal End Distance:** Between 2.538 inches and 2.722 inches **Pole Quantity:** 1 **Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:**

Trip free

NSN 5925-01-195-2013

Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.050 at 200 pct single location and 1.900 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Frequency In Hertz:
60.0 single location
Unpackaged Unit Weight:
4.000 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0