## NSN 5925-01-196-2083

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-196-2083

Thread Pitch Diameters:
Tilleau Filcii Diameters.
+0.3503/+0.3537 inches
Body Style:
Multipole-single actuator type
Bushing Length:
0.380 inches
Body Length:
1.562 inches
Body Width:
1.937 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
0.900 inches
Center To Center Distance Between Terminals Parallel To Width:
0.625 inches
Switch Contact Arrangement:
Single pole, double throw
Mounting Surface To Terminal End Distance:
1.828 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
A three-dead brooking roofs and
1 threaded bushing w/panel seal
Storage Type:
Storage Type:
Storage Type: General purpose warehouse
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi):
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole:
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 2.5 amperes ac all locations
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 2.5 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts:
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 2.5 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac all locations
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 2.5 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 2.5 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 2.5 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations Circuit Protection Type:
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 2.5 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations Circuit Protection Type: Overcurrent all locations
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 2.5 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method:
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 2.5 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 2.5 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations Trip Release Characteristic:

## NSN 5925-01-196-2083

Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Auxiliary Switch Function And Quantity:
1 alarm
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Switch Location And Position Designation:
Internal at pole three
Trip Delay Time In Seconds Per Rated Continuous Current:
0.055 at 200 pct all locations and 0.950 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Hermetically sealed
Switch Terminal Type:
Tab, solder lug
Switch Current Rating And Type In Amps:
0.5 ac and 0.5 dc
Switch Voltage Rating And Type In Volts:
120.0 ac and 50.0 dc
Frequency In Hertz:
60.0 all locations
Thread Series Designator:
Unef
Terminal Type And Quantity:
6 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0