

View Online at <https://aerobasegroup.com/nsn/5925-01-196-5123>

Body Style:

Multipole-multiple actuator type

Bushing Length:

0.040 inches

Body Length:

2.130 inches

Body Width:

1.650 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.960 inches

Center To Center Distance Between Terminals Parallel To Width:

0.740 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.950 inches

Mounting Surface To Terminal End Distance:

1.610 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 clip

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations and 5.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations and 28.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

50.0 ac all locations and 50.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct all locations and 40.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Corrosion resistant

Trip Release Ambient Temperature Rating:

-35.0 degrees celsius all locations and 55.0 degrees celsius all locations

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Terminal Type And Quantity:

4 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0