

View Online at <https://aerobasegroup.com/nsn/5925-01-197-4165>

**Body Style:**

Single pole type

**Body Length:**

2.000 inches

**Body Width:**

0.750 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.750 inches and 1.562 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.660 inches

**End Application:**

6530-01-147-9531

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 threaded hole

**Cubic Measure:**

0.031 cubic feet

**Maximum Continuous Load Current Rating Per Pole:**

30.0 amperes ac single location and 30.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location and 65.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac single location and 1000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Instantaneous single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 single location

**Ultimate Trip Time Per Pole In Seconds:**

0.004 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

As

**Internal Trip Release Configuration:**

Relay trip single location

**Thread Size:**

0.109 inches

**Special Features:**

Actuator is white plastic with on-off in black 0.125 inch lettering hot stamped on face, o/a dim. 0.750 in. Wide, 1.185 in. Long

**Frequency In Hertz:**

50.0 first location

**Unpackaged Unit Weight:**

0.140 pounds

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 quick disconnect, male

**Purchase Description Identification:**

02964-p84386-001

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0