

View Online at <https://aerobasegroup.com/nsn/5925-01-197-4165>

Body Style:

Single pole type

Body Length:

2.000 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.750 inches and 1.562 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

End Application:

6530-01-147-9531

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Cubic Measure:

0.031 cubic feet

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac single location and 30.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location and 65.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location and 1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 single location

Ultimate Trip Time Per Pole In Seconds:

0.004 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Actuator Position Designation:

As

Internal Trip Release Configuration:

Relay trip single location

Thread Size:

0.109 inches

Special Features:

Actuator is white plastic with on-off in black 0.125 inch lettering hot stamped on face, o/a dim. 0.750 in. Wide, 1.185 in. Long

Frequency In Hertz:

50.0 first location

Unpackaged Unit Weight:

0.140 pounds

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 quick disconnect, male

Purchase Description Identification:

02964-p84386-001

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0