

View Online at <https://aerobasegroup.com/nsn/5925-01-197-4686>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

4.260 inches

**Overall Height:**

1.200 inches

**Overall Width:**

3.250 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.172 inches

**Switch Contact Arrangement:**

Single pole, double throw

**End Application:**

1520-01-125-5476

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes ac single location and 10.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

115.0 ac single location and 28.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

3600.0 ac single location and 3600.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 single location

**Reset Method:**

Automatic

**Main Contact Tripping Mechanism Type:**

Trip free

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Series trip single location

**Switch Location And Position Designation:**

Internal at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

12.000 at 200 pct single location and 42.000 at 200 pct single location

**Incllosure Protection Type For Which Designed:**

Fungus proof

**Trip Release Ambient Temperature Rating:**

-54.0 degrees celsius single location and 71.0 degrees celsius single location

**Switch Terminal Type:**

Quick disconnect, female

**Switch Current Rating And Type In Amps:**

5.0 ac and 5.0 dc

**Switch Voltage Rating And Type In Volts:**

115.0 ac and 28.0 dc

**Frequency In Hertz:**

400.0 single location

**Test Data Document:**

81349-mil-c-83383 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 threaded stud

**Specification Data:**

81349-mil-c-83383/2 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0