

View Online at <https://aerobasegroup.com/nsn/5925-01-197-9436>

Body Style:

Single pole type

Mounting Slot Width:

0.370 inches

Body Length:

6.312 inches

Body Width:

1.375 inches

Body Height:

3.375 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

5.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

End Application:

An/fps-117 radar set

Boss Height:

0.250 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

4 slot

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location and 15.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location and 125.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac single location and 10000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Reset

Actuator Position Designation:

At pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

0.350 at 200 pct single location

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

40.0 degrees fahrenheit single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0