NSN 5925-01-197-9437

Circuit Breaker - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5925-01-197-9437

Single pole type
Mounting Slot Width:
0.375 inches
Body Length:
6.312 inches
Body Width:
1.375 inches
Body Height:
3.812 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
5.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
4.875 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.000 inches
Boss Height:
0.187 inches
Pole Quantity:
1
Manustina Facility Type And Overtity
Mounting Facility Type And Quantity:
4 slot
4 slot
4 slot Storage Type:
4 slot Storage Type: General purpose warehouse
4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole:
4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location
4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts:
4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac single location and 125.0 dc single location
4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 5000.0 dc single location
4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 5000.0 dc single location Circuit Protection Type:
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 5000.0 dc single location Circuit Protection Type: Overcurrent single location
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 5000.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method:
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 5000.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal-magnetic single location
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 5000.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal-magnetic single location Trip Release Characteristic:
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 5000.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal-magnetic single location Trip Release Characteristic: Instantaneous single location
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 5000.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal-magnetic single location Trip Release Characteristic: Instantaneous single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

NSN 5925-01-197-9437 Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius single location
Frequency In Hertz:
60.0 single location
Unpackaged Unit Weight:
1.300 pounds
Terminal Type And Quantity:
2 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0