## NSN 5925-01-198-6220

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-198-6220

## Body Style:

Multipole-single actuator type

## **Bushing Length:**

Between 0.219 inches and 0.281 inches

## Body Length:

Between 0.730 inches and 0.770 inches

#### Body Width:

1.840 inches

#### **Body Height:**

Between 1.319 inches and 1.381 inches

#### Case Material:

Metal

#### Center To Center Distance Between Terminals Parallel To Length:

Between 0.469 inches and 0.531 inches

Center To Center Distance Between Terminals Parallel To Width:

## Between 0.593 inches and 0.655 inches

#### **Fragility Factor:**

Moderately rugged

#### Pole Quantity:

3

## Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

#### Storage Type:

General purpose warehouse

#### **Special Handling Feature:**

Magnetic

## Thready Qty Per Inch (tpi):

32

## Maximum Continuous Load Current Rating Per Pole:

7.5 amperes ac all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

175.0 ac all locations

## Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

## Trip Release Method:

Thermal all locations

#### **Trip Release Characteristic:**

Time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

145.0 all locations

# NSN 5925-01-198-6220

Circuit Breaker - Page 2 of 2

Reset Method:
Main Contact Tripping Mechanism Type:
Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.438 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
4.000 at 200 pct all locations and 20.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Shock resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
400.0 all locations
Unpackaged Unit Weight:
65.0 grams
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Thread Series Designator:
Uns
Terminal Type And Quantity:
6 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0

