## NSN 5925-01-198-6220

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-198-6220

**Body Style:** 

Multipole-single actuator type

**Bushing Length:** 

Between 0.219 inches and 0.281 inches

**Body Length:** 

Between 0.730 inches and 0.770 inches

**Body Width:** 

1.840 inches

**Body Height:** 

Between 1.319 inches and 1.381 inches

**Case Material:** 

Metal

**Center To Center Distance Between Terminals Parallel To Length:** 

Between 0.469 inches and 0.531 inches

**Center To Center Distance Between Terminals Parallel To Width:** 

Between 0.593 inches and 0.655 inches

**Fragility Factor:** 

Moderately rugged

**Pole Quantity:** 

2

**Mounting Facility Type And Quantity:** 

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

**Special Handling Feature:** 

Magnetic

Thready Qty Per Inch (tpi):

**Maximum Continuous Load Current Rating Per Pole:** 

7.5 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:** 

175.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

**Circuit Protection Type:** 

Overcurrent all locations

**Trip Release Method:** 

Thermal all locations

**Trip Release Characteristic:** 

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

145.0 all locations

## NSN 5925-01-198-6220

Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.438 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
4.000 at 200 pct all locations and 20.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Shock resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
400.0 all locations
Unpackaged Unit Weight:
65.0 grams
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Thread Series Designator:
Uns
Terminal Type And Quantity:
6 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0