

View Online at <https://aerobasegroup.com/nsn/5925-01-198-8981>

Body Style:

Multipole-multiple actuator type

Body Length:

2.500 inches

Body Width:

2.280 inches

Body Height:

2.540 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

2.060 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.940 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Boss Height:

0.300 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

2 threaded stud

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location and 250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

Manual Actuator Type And Quantity:

3 push-pull

Actuator Function:

Reset

Actuator Position Designation:

At each pole

Internal Trip Release Configuration:

Shunt trip single location

Thread Size:

0.190 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 125 pct single location

Trip Release Ambient Temperature Rating:

-48.0 degrees celsius single location and 90.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Thread Series Designator:

Unf

Terminal Type And Quantity:

3 eyelet

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0