

View Online at <https://aerobasegroup.com/nsn/5925-01-200-1701>

**Body Style:**

Rectangular dimensional envelope

**Case Material:**

Metal

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

3

**Arc Quenching Method:**

Air

**Storage Type:**

General purpose warehouse

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

3200.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

85000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+4800.0/+8000.0 ac all locations

**Internal Trip Release Configuration:**

Series trip all locations

**Inclosure Protection Type For Which Designed:**

Dustproof

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0