

View Online at <https://aerobasegroup.com/nsn/5925-01-200-1960>

Body Style:

Rectangular dimensional envelope

Case Material:

Metal

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Arc Quenching Method:

Air

Storage Type:

General purpose warehouse

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

480.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

34000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Adjustable Trip Setting Current Range Per Pole In Amps:

+960.0/+1280.0 ac all locations

Internal Trip Release Configuration:

Series trip all locations

Inclosure Protection Type For Which Designed:

Dustproof

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0