

View Online at <https://aerobasegroup.com/nsn/5925-01-200-7813>

**Body Style:**

Multipole-single actuator type

**Body Length:**

6.500 inches

**Body Width:**

4.125 inches

**Body Height:**

4.688 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

3.938 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.343 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.313 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.375 inches

**Boss Height:**

0.188 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 threaded stud

**Features Provided:**

High inrush protection

**Maximum Continuous Load Current Rating Per Pole:**

100.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

135.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Thread Size:**

0.190 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

40.000 at 400 pct all locations

**Inclosure Protection Type For Which Designed:**

General purpose

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Special Features:**

Special generator application

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0