

View Online at <https://aerobasegroup.com/nsn/5925-01-201-9171>

Body Style:

Single pole type

Bushing Length:

0.468 inches

Body Length:

1.375 inches

Body Width:

0.680 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.125 inches

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.355 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.555 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

0.500 amperes ac single location and 0.500 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location and 50.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location and 1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.500 inches

Inclosure Protection Type For Which Designed:

General purpose

Frequency In Hertz:

50.0 single location or 60.0 single location

Unpackaged Unit Weight:

1.200 ounces

Thread Series Designator:

Un

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0