NSN 5925-01-202-0131

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-202-0131

Body Style:

Multipole-single actuator type

Bushing Length:

0.130 inches

Body Length:

2.000 inches

Body Width:

1.500 inches

Body Height:

1.930 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.560 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

NSN 5925-01-202-0131 Circuit Breaker - Page 2 of 2



| Trip Release Method: |
|--|
| Magnetic-hydraulic all locations |
| Trip Release Characteristic: |
| Time delay all locations |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 125.0 all locations |
| Reset Method: |
| Manual |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| Manual Actuator Type And Quantity: |
| 1 toggle |
| Actuator Function: |
| Trip-reset |
| Actuator Position Designation: |
| At pole one |
| Internal Trip Release Configuration: |
| Series trip all locations |
| Thread Size: |
| 3.0 millimeters |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 2.500 at 200 pct all locations and 20.000 at 200 pct all locations |
| Inclosure Protection Type For Which Designed: |
| Fungus resistant and moisture resistant |
| Frequency In Hertz: |
| 50.0 all locations or 60.0 all locations |
| Unpackaged Unit Weight: |
| 5.000 ounces |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 4 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |