NSN 5925-01-202-1786

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-202-1786

Body	Style:

Single pole type

Body Length:

2.250 inches

Body Width:

1.000 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.781 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.750 inches

Mounting Surface To Terminal End Distance:

2.250 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 terminal

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

65.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Ultimate Trip Time Per Pole In Seconds:

6.500 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

NSN 5925-01-202-1786

Circuit Breaker - Page 2 of 2



Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 125 pct single location

Terminal Type And Quantity:

2 knife blade

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0