NSN 5925-01-204-3361

Circuit Breaker - Page 1 of 2

Body Style:Single pole type



View Online at https://aerobasegroup.com/nsn/5925-01-204-3361

Body Length:
3.719 inches
Body Width:
0.990 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
3.063 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.750 inches
Switch Contact Arrangement:
Single pole, double throw
Fragility Factor:
Moderately rugged
Boss Height:
0.156 inches
Mounting Surface To Terminal End Distance:
3.243 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 threaded hole
Storage Type:
Storage Type: General purpose warehouse
General purpose warehouse
General purpose warehouse Maximum Continuous Load Current Rating Per Pole:
General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 30.0 amperes dc single location
General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 30.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts:
General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 30.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 125.0 dc single location
General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 30.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 30.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 dc single location
General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 30.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 dc single location Circuit Protection Type:
General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 30.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 dc single location Circuit Protection Type: Overcurrent single location
General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 30.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method:
General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 30.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic-hydraulic single location
General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 30.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic-hydraulic single location Trip Release Characteristic:
General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 30.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic-hydraulic single location Trip Release Characteristic: Time delay single location
Maximum Continuous Load Current Rating Per Pole: 30.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic-hydraulic single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

NSN 5925-01-204-3361

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Auxiliary Switch Function And Quantity:
1 control
nternal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Switch Location And Position Designation:
nternal at pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
4.000 at 300 pct single location and 10.500 at 300 pct single location
nclosure Protection Type For Which Designed:
General purpose
Precious Material And Location:
Auxiliary switch contacts surface treatment gold and breaker contact surface silver and breaker terminal hardware surfaces silver
Precious Material:
Gold and silver
Γhread Series Designator:
Jnc
Ferminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A030a0