

View Online at <https://aerobasegroup.com/nsn/5925-01-204-9438>

Body Style:

Single pole type

Overall Length:

3.375 inches

Body Width:

1.250 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

1.531 inches

Unthreaded Mounting Hole Diameter:

Between 0.195 inches and 0.201 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.927 inches and 2.947 inches

Switch Contact Arrangement:

Single pole, single throw, normally closed

Mounting Surface To Terminal End Distance:

4.250 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Features Provided:

Trip indicator

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2800.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Auxiliary Trip Coil Voltage Type And Rating In Volts:

28.0 dc single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Time Per Pole In Seconds:

360.000 single location

Reset Method:

Electric

Main Contact Tripping Mechanism Type:

Nontrip free

Auxiliary Switch Function And Quantity:

1 control

Internal Trip Release Configuration:

Series trip w/remote trip feature single location

Trip Release Duty Cycle:

Continuous single location

Switch Location And Position Designation:

External at pole one

Reset Actuator Voltage Rating And Type In Volts:

7.5 dc

Trip Delay Time In Seconds Per Rated Continuous Current:

13.000 at 200 pct single location and 60.000 at 200 pct single location

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Switch Terminal Type:

Wire lead

Switch Current Rating And Type In Amps:

15.0 dc

Switch Voltage Rating And Type In Volts:

28.0 dc

Terminal Type And Quantity:

2 tab w/screw

Specification Data:

36659-Is10071 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0