NSN 5925-01-204-9441

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-204-9441

| Body Style: |
|--|
| Single pole type |
| Overall Length: |
| 3.375 inches |
| Body Width: |
| 1.250 inches |
| Case Material: |
| Metal |
| Center To Center Distance Between Terminals Parallel To Length: |
| 1.531 inches |
| Unthreaded Mounting Hole Diameter: |
| Between 0.195 inches and 0.201 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| Between 2.927 inches and 2.947 inches |
| Switch Contact Arrangement: |
| Single pole, single throw, normally closed |
| Mounting Surface To Terminal End Distance: |
| 4.250 inches |
| Pole Quantity: |
| 1 |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole |
| Features Provided: |
| Trip indicator |
| Maximum Continuous Load Current Rating Per Pole: |
| 7.5 amperes ac single location |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 115.0 ac single location |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 2800.0 ac single location |
| Circuit Protection Type: |
| Overcurrent single location |
| Trip Release Method: |
| Thermal single location |
| Auxiliary Trip Coil Voltage Type And Rating In Volts: |
| 110.0 ac single location |
| Trip Release Characteristic: |
| Time delay single location |
| Ultimate Trip Time Per Pole In Seconds: |
| 360.000 single location |
| Reset Method: |

Electric

NSN 5925-01-204-9441 Circuit Breaker - Page 2 of 2



| Main Contact Tripping Mechanism Type: |
|---|
| Nontrip free |
| Auxiliary Switch Function And Quantity: |
| 1 control |
| Internal Trip Release Configuration: |
| Series trip w/remote trip feature single location |
| Trip Release Duty Cycle: |
| Continuous single location |
| Switch Location And Position Designation: |
| External at pole one |
| Reset Actuator Voltage Rating And Type In Volts: |
| 110.0 ac |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 13.000 at 200 pct single location and 60.000 at 200 pct single location |
| Trip Release Ambient Tempurature Rating: |
| 25.0 degrees celsius single location |
| Switch Terminal Type: |
| Wire lead |
| Switch Current Rating And Type In Amps: |
| 7.5 ac |
| Switch Voltage Rating And Type In Volts: |
| 110.0 ac |
| Terminal Type And Quantity: |
| 2 tab w/screw |
| Specification Data: |
| 36659-ls10071 manufacturers specification control |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |
| |