## NSN 5925-01-205-1542

Circuit Breaker - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5925-01-205-1542

Single pole type
Overall Length:
2.400 inches
Body Width:
0.866 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
0.906 inches
Unthreaded Mounting Hole Diameter:
0.190 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.050 inches
Mounting Surface To Terminal End Distance:
0.810 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
10.0 amperes ac single location
Operating Voltage Type And Rating Per Pole In Volts:
250.0 ac single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
60.0 ac single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Automatic
Internal Trip Release Configuration:
Series trip single location
Trip Delay Time In Seconds Per Rated Continuous Current:
20.000 at 200 pct single location and 45.000 at 200 pct single location

## NSN 5925-01-205-1542

Circuit Breaker - Page 2 of 2



## Inclosure Protection Type For Which Designed:

Fungus resistant

**Trip Release Ambient Tempurature Rating:** 

25.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

**Unpackaged Unit Weight:** 

0.750 ounces

**Terminal Type And Quantity:** 

2 quick disconnect, male

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A030a0