NSN 5925-01-205-2848

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-205-2848 **Body Style:** Multipole-single actuator type **Body Length:** 2.000 inches **Body Width:** 1.540 inches **Body Height:** 1.770 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 0.620 inches **Boss Height:** 0.125 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 clip Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 5.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic-hydraulic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:**

1 toggle **Actuator Function:** Trip-reset

NSN 5925-01-205-2848

Circuit Breaker - Page 2 of 2

Fiig: A030a0



Actuator Position Designation:
Between pole one and two
Internal Trip Release Configuration:
Series trip all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
0.150 at 200 pct all locations and 8.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
4 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No