

View Online at <https://aerobasegroup.com/nsn/5925-01-205-2849>

**Body Style:**

Multipole-single actuator type

**Body Length:**

2.000 inches

**Body Width:**

1.310 inches

**Body Height:**

1.770 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Width:**

0.620 inches

**Boss Height:**

0.125 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

4 clip

**Storage Type:**

General purpose warehouse

**Features Provided:**

High inrush protection

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

Between pole one and two

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

1.500 at 200 pct all locations and 8.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Shockproof

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0