

View Online at <https://aerobasegroup.com/nsn/5925-01-205-2851>

Body Style:

Single pole type

Body Length:

1.775 inches

Overall Diameter:

0.750 inches

Case Material:

Plastic

Nonturn Device Location:

At 9 oclock

Fragility Factor:

Moderately rugged

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 clip

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

9.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

50.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

200.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

1.500 at 200 pct single location and 12.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

General purpose

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0