

View Online at <https://aerobasegroup.com/nsn/5925-01-205-7480>

Body Style:

Single pole type

Bushing Length:

0.277 inches

Body Length:

Between 0.719 inches and 0.781 inches

Body Width:

Between 0.531 inches and 0.593 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

Between 0.742 inches and 0.804 inches

Switch Contact Arrangement:

Single pole, single throw, normally closed

Mounting Surface To Terminal End Distance:

Between 1.287 inches and 1.317 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

0.5 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

100.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

145.0 single location

Ultimate Trip Time Per Pole In Seconds:

2.000 single location and 20.000 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 control

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.469 inches

Switch Location And Position Designation:

External at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct single location and 20.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Explosion resistant and moisture resistant and vibration resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Switch Terminal Type:

Turret

Switch Current Rating And Type In Amps:

0.5 ac

Switch Voltage Rating And Type In Volts:

115.0 ac

Frequency In Hertz:

2000.0 single location

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 screw

Specification Data:

36659-Is10187 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0