NSN 5925-01-206-9417

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-206-9417

| view Online at https://aeiobasegroup.com/nsn/5925-01-200-9417 |
|--|
| Body Style: |
| Single pole type |
| Overall Length: |
| 80.16 millimeters |
| Body Width: |
| 47.6 millimeters |
| Case Material: |
| Plastic |
| Center To Center Distance Between Terminals Parallel To Length: |
| 27.0 millimeters |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 61.11 millimeters |
| Fragility Factor: |
| Moderately rugged |
| Pole Quantity: |
| 1 |
| Mounting Facility Type And Quantity: |
| 2 threaded stud |
| Maximum Continuous Load Current Rating Per Pole: |
| 80.0 amperes dc single location |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 110.0 dc single location |
| Circuit Protection Type: |
| Overcurrent single location |
| Trip Release Method: |
| Thermal single location |
| Trip Release Characteristic: |
| Time delay single location |
| Reset Method: |
| Manual |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| Manual Actuator Type And Quantity: |
| 1 push button |
| Actuator Function: |
| Reset |
| Actuator Position Designation: |
| At pole one |
| Thread Size: |
| 0.138 inches |
| Inclosure Protection Type For Which Designed: |

General purpose

NSN 5925-01-206-9417

Circuit Breaker - Page 2 of 2



Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0