

View Online at <https://aerobasegroup.com/nsn/5925-01-207-5008>

Body Style:

Multipole-single actuator type

Body Length:

10.125 inches

Body Width:

8.250 inches

Body Height:

3.812 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

9.120 inches

Center To Center Distance Between Terminals Parallel To Width:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.410 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

7.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.750 inches

End Application:

Used onboard 110 ft wpb coast guard vessels

Boss Height:

0.500 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

200.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

220.0 ac all locations

Circuit Protection Type:

Undervoltage all locations

Trip Release Method:

Solid state all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

110.0 all locations

Ultimate Trip Time Per Pole In Seconds:

3.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0