NSN 5925-01-208-1967

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-208-1967 **Body Style:** Single pole type **Bushing Length:** 0.380 inches **Body Length:** 1.562 inches **Body Width:** 1.281 inches **Case Material:** Metal **Center To Center Distance Between Terminals Parallel To Length:** 0.875 inches **Switch Contact Arrangement:** Single pole, double throw **Mounting Surface To Terminal End Distance:** 1.780 inches **Pole Quantity:** 1 **Mounting Facility Type And Quantity:** 1 threaded bushing w/panel seal Storage Type: General purpose warehouse **Features Provided:** High inrush protection Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

NSN 5925-01-208-1967

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Auxiliary Switch Function And Quantity:
1 alarm
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.375 inches
Switch Location And Position Designation:
Internal at pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
0.200 at 200 pct and 1.700 at 200 pct single location
Inclosure Protection Type For Which Designed:
Hermetically sealed
Switch Terminal Type:
Tab, solder lug
Switch Current Rating And Type In Amps:
0.5 ac and 0.5 dc
Switch Voltage Rating And Type In Volts:
120.0 ac and 50.0 dc
Frequency In Hertz:
50.0 or 60.0 single location
Unpackaged Unit Weight:
1.800 ounces
Thread Series Designator:
Unef
Terminal Type And Quantity:
2 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0