

View Online at <https://aerobasegroup.com/nsn/5925-01-209-2764>

Thread Pitch Diameters:

+0.4752/+0.4787 inches

Body Style:

Multipole-single actuator type

Bushing Length:

0.625 inches

Body Length:

2.000 inches

Body Width:

2.250 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Nonturn Device Location:

At 12 oclock and at 9 oclock and at 3 oclock

Nonturn Device Radius:

0.656 inches

Nonturn Device Length:

0.130 inches

Nonturn Device Diameter:

Between 0.151 inches and 0.161 inches

Switch Contact Arrangement:

Single pole, double throw

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

2.232 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

4.0 amperes dc second location

Operating Voltage Type And Rating Per Pole In Volts:

65.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.500 inches

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

0.024 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Hermetically sealed and shock resistant and vibration resistant

Switch Terminal Type:

Quick disconnect, male

Switch Current Rating And Type In Amps:

10.0 ac and 5.0 dc

Switch Voltage Rating And Type In Volts:

250.0 ac and 30.0 dc

Unpackaged Unit Weight:

9.000 ounces

Thread Series Designator:

Un

Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0