NSN 5925-01-211-7740



Circuit Breaker Tripper - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-211-7740 **Body Style:** Rectangular dimensional envelope **Overall Length:** 4.220 inches **Overall Height:** 0.660 inches **Overall Width:** 1.900 inches **Fragility Factor:** Moderately rugged **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 1 threaded bushing Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 4.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 12.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Instantaneous single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Manual Actuator Type And Quantity:** 1 push-pull **Actuator Function: Actuator Position Designation:**

Trip-reset At pole one **Internal Trip Release Configuration:**

Relay trip single location

NSN 5925-01-211-7740

Circuit Breaker Tripper - Page 2 of 2



0.484 inches
Thread Series Designator:
Uns

Thread Size:

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0