NSN 5925-01-212-1490

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-212-1490

Body Style:

Single pole type

Body Length:

Between 1.968 inches and 2.032 inches

Body Width:

Between 0.718 inches and 0.782 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.528 inches and 1.592 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.628 inches and 1.692 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.098 inches and 1.062 inches

Mounting Surface To Terminal End Distance:

Between 2.593 inches and 2.657 inches

Pole Quantity:

_

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

. . . . ou

32

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

NSN 5925-01-212-1490 Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Relay trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.160 at 200 pct and 1.600 at 200 pct single location
Inclosure Protection Type For Which Designed:
Humidity resistant and shock resistant and vibration resistant
Frequency In Hertz:
50.0 or 60.0 single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0