NSN 5925-01-213-1342

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-213-1342

Body Style:
Multipole-single actuator type
Bushing Length:
0.380 inches
Body Length:
1.500 inches
Body Width:
1.250 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
0.875 inches
Center To Center Distance Between Terminals Parallel To Width:
0.625 inches
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
0.625 inches
Nonturn Device Length:
0.130 inches
Nonturn Device Diameter:
0.140 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
1.780 inches
Pole Quantity:
2
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
1 threaded bushing w/panel seal
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Features Provided:
High inrush protection
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:

Maximum Continuous Load Current Rating Per Pole

2.5 amperes ac all locations

NSN 5925-01-213-1342

Circuit Breaker - Page 2 of 2



Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.200 at 200 pct and 1.700 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Hermetically sealed
Frequency In Hertz:
50.0 or 60.0 all locations
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 wire hook
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:

A030a0