NSN 5925-01-213-4197

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-213-4197

Body Style: Multipole-multiple actuator type Body Length: Between 2.480 inches and 2.500 inches

Body Width:

2.265 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 2.925 inches and 2.955 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.735 inches and 0.765 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.050 inches and 2.070 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.735 inches and 0.765 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.135 inches and 0.165 inches

Mounting Surface To Terminal End Distance:

2.000 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

6 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

300.0 amperes ac and 300.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

 $350.0 \mbox{ ac} \ \mbox{and} \ 350.0 \mbox{ dc} \ \mbox{all locations}$

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac and 1000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

NSN 5925-01-213-4197

Circuit Breaker - Page 2 of 2



Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
150.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
3 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, and three linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Inclosure Protection Type For Which Designed:
Corrosion resistant and moisture resistant and shock resistant and vibration resistant
Special Features:
Protection barriers between poles
Frequency In Hertz:
400.0 all locations
Unpackaged Unit Weight:
11.100 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0