## NSN 5925-01-213-6398



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-213-6398 **Body Style:** Multipole-single actuator type **Bushing Length:** 0.468 inches **Body Length:** 1.375 inches **Body Width:** 1.304 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 1.125 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.625 inches **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.222 inches **Nonturn Device Width:** 0.028 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 1.702 inches **Pole Quantity:** 2

**Arc Quenching Method:** 

**Mounting Facility Type And Quantity:** 

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

**Maximum Continuous Load Current Rating Per Pole:** 

7.5 amperes ac and 7.5 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:** 

250.0 ac and 50.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 

1000.0 ac and 1000.0 dc all locations

**Circuit Protection Type:** 

Overcurrent all locations

## **NSN 5925-01-213-6398** Circuit Breaker - Page 2 of 2



Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
138.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.500 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.100 at 200 pct and 2.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Special Features:
Paddle handle
Frequency In Hertz:
50.0 or 60.0 all locations
Thread Series Designator:
Uns
Terminal Type And Quantity:
4 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A030a0